

Hash-based indexes

Iztok Savnik, FAMNIT

Slides & Textbook


- Textbook:
 - Raghu Ramakrishnan, Johannes Gehrke, *Database Management Systems*, McGraw-Hill, 3rd ed., 2007.
- Slides:
 - From „Cow Book“: R.Ramakrishnan, <http://pages.cs.wisc.edu/~dbbook/>

Introduction

- As for any *index*, 3 *alternatives for data entries k^** :
 - Data record with key value k
 - $\langle k, \text{rid of data record with search key value } k \rangle$
 - $\langle k, \text{list of rids of data records with search key } k \rangle$
 - Choice orthogonal to the *indexing technique*
- Hash-based indexes are best for *equality selections*. **Cannot** support range searches.
- Static and dynamic hashing techniques exist; trade-offs similar to ISAM vs. B+ trees.

Static Hashing

- # primary pages fixed, allocated sequentially, never de-allocated; overflow pages if needed.
- $h(k) \bmod M$ = bucket to which data entry with key k belongs. ($M = \#$ of buckets)



Static Hashing (Contd.)


- Buckets contain *data entries*.
- Hash fn works on *search key* field of record r .
Must distribute values over range $0 \dots M-1$.
 - $h(\text{key}) = (a * \text{key} + b)$ usually works well.
 - a and b are constants; lots known about how to tune h .
- **Long overflow chains** can develop and degrade performance.
 - *Extendible* and *Linear Hashing*: Dynamic techniques to fix this problem.

Extendible Hashing

- Situation: Bucket (primary page) becomes full.
Why not re-organize file by *doubling* # of buckets?
 - Reading and writing all pages is expensive!
 - Idea: Use *directory of pointers to buckets*, double # of buckets by *doubling the directory*, splitting just the bucket that overflowed!
 - Directory much smaller than file, so doubling it is much cheaper. Only one page of data entries is split. *No overflow page!*
 - Trick lies in how hash function is adjusted!



Example ➔

- Directory is array of size 4.
- To find bucket for r , take last *global depth* # bits of $\mathbf{h}(r)$; we denote r by $\mathbf{h}(r)$.
 - If $\mathbf{h}(r) = 5 = \text{binary } 101$, it is in bucket pointed to by 01.



- ❖ **Insert:** If bucket is full, *split* it (*allocate new page, re-distribute*).
- ❖ *If necessary, double the directory.* (As we will see, splitting a bucket does not always require doubling; we can tell by comparing *global depth* with *local depth* for the split bucket.)

Insert $h(r)=20$ (Causes Doubling)




Points to Note

- $20 = \text{binary } 10100$. Last **2** bits (00) tell us r belongs in A or A2. Last **3** bits needed to tell which.
 - *Global depth of directory*: Max # of bits needed to tell which bucket an entry belongs to.
 - *Local depth of a bucket*: # of bits used to determine if an entry belongs to this bucket.
- When does bucket split cause directory doubling?
 - Before insert, *local depth* of bucket = *global depth*. Insert causes *local depth* to become $>$ *global depth*; directory is doubled by *copying it over* and `fixing' pointer to split image page. (Use of least significant bits enables efficient doubling via copying of directory!)


Directory Doubling

Why use least significant bits in directory?
» Allows for doubling via copying!

$$6 = 110$$



$$6 = 110$$



Least Significant

IDB, Indexes

vs.

Most Significant

Comments on Extendible Hashing

- If directory fits in memory, equality search answered with one disk access; else two.
 - 100MB file, 100 bytes/rec, 4K pages contains 1,000,000 records (as data entries) and 25,000 directory elements; chances are high that directory will fit in memory.
 - Directory grows in spurts, and, if the distribution *of hash values* is skewed, directory can grow large.
 - Multiple entries with same hash value cause problems!
- **Delete**: If removal of data entry makes bucket empty, can be merged with 'split image'. If each directory element points to same bucket as its split image, can halve directory.

Linear Hashing


- This is another dynamic hashing scheme, an alternative to Extendible Hashing.
- LH handles the problem of long overflow chains without using a directory, and handles duplicates.
- Idea: Use a family of hash functions h_0, h_1, h_2, \dots
 - $h_i(key) = h(key) \text{ mod}(2^i N)$; $N = \text{initial \# buckets}$
 - h is some hash function (range is *not* 0 to $N-1$)
 - If $N = 2^{d_0}$, for some d_0 , h_i consists of applying h and looking at the last d_i bits, where $d_i = d_0 + i$.
 - h_{i+1} doubles the range of h_i (similar to directory doubling)

Linear Hashing (Contd.)

- Directory avoided in LH by using overflow pages, and choosing bucket to split round-robin.
 - **Splitting proceeds in `rounds'.** Round ends when all N_R initial (for round R) buckets are split. Buckets 0 to $Next-1$ have been split; $Next$ to N_R yet to be split.
 - **Current round number is $Level$.**
 - **Search:** To find bucket for data entry r , find $h_{Level}(r)$:
 - If $h_{Level}(r)$ in range `Next to N_R ', r belongs here.
 - Else, r could belong to bucket $h_{Level}(r)$ or bucket $h_{Level}(r) + N_R$; must apply $h_{Level+1}(r)$ to find out.

Overview of LH File

- In the middle of a round.





Linear Hashing (Contd.)


- **Insert:** Find bucket by applying $h_{Level} / h_{Level+1}$:
 - If bucket to insert into is full:
 - Add overflow page and insert data entry.
 - (Maybe) Split *Next* bucket and increment *Next*.
- Can choose any criterion to ‘trigger’ split.
- Since buckets are split round-robin, long overflow chains don’t develop!
- Doubling of directory in Extendible Hashing is similar; switching of hash functions is *implicit* in how the # of bits examined is increased.

Example of Linear Hashing

- On split, $h_{\text{Level}+1}$ is used to re-distribute entries.



Example: End of a Round



LH Described as a Variant of EH

- The two schemes are actually quite similar:
 - Begin with an EH index where directory has N elements.
 - Use overflow pages, split buckets round-robin.
 - First split is at bucket 0. (Imagine directory being doubled at this point.) But elements $\langle 1, N+1 \rangle, \langle 2, N+2 \rangle, \dots$ are the same. So, need only create directory element N , which differs from 0, now.
 - When bucket 1 splits, create directory element $N+1$, etc.
- So, directory can double gradually. Also, primary bucket pages are created in order. If they are *allocated* in sequence too (so that finding i 'th is easy), we actually don't need a directory! Voila, LH.

Summary

- Hash-based indexes: best for equality searches, cannot support range searches.
- Static Hashing can lead to long overflow chains.
- Extendible Hashing avoids overflow pages by splitting a full bucket when a new data entry is to be added to it. *(Duplicates may require overflow pages.)*
 - Directory to keep track of buckets, doubles periodically.
 - Can get large with skewed data; additional I/O if this does not fit in main memory.

Summary (Contd.)

- Linear Hashing avoids directory by splitting buckets round-robin, and using overflow pages.
 - Overflow pages not likely to be long.
 - Duplicates handled easily.
 - Space utilization could be lower than Extendible Hashing, since splits not concentrated on 'dense' data areas.
 - Can tune criterion for triggering splits to trade-off slightly longer chains for better space utilization.
- For hash-based indexes, a *skewed* data distribution is one in which the *hash values* of data entries are not uniformly distributed!